HiLo PowerTilt



TOP:

Top design Four-piece adjustable top with round corners, three-layer foam, 3/4" plywood

Standard size top 30" x 73"

Foam 2" firm bottom layer + 1- 3/4" medium-density layer of urethane polymer

Polyester batting 1/2" fluffy polyester Dacron top layer

Frame 3/4" plywood frame reinforced for arm rests and face cradle

Motorized adjustment of height from 17" to 36" (ADA compliant), and

motorized adjustments of torso, knee, and upper body sections

Back tilt angle 0 to 60° Knee tilt angle 0 to 30°




Adjustments

Carbon steel base Sleek, contemporary design with white powder-coat finish

8" leg recess 8" recess from ends of table

Height range - standard 17" to 36" (infinite motorized adjustment)

Weight capacity Lifting weight capacity 450 lbs.; static weight capacity 500 lbs.



PowerTilt motors Two 24v DC, 5 amp max motor/actuators, UL recognized;

powered through a 110v, 5 amp transformer

Main lift mechanism One 24v DC, 5 amp max motor/actuator, UL recognized

(uses the same transformer as the top motor/actuators)

Not warranted, but guaranteed to arrive in good condition

Controls Hand control

VINYL:

UltraSoft-Touch - standard Lightly textured, super-soft PU vinyl, fabric backed, PVC-free

ACCESSORIES:

Sidearms Flex Armrests
Face support Deluxe FaceSpace II

Foot extension Salon Footrest or Full Footrest

Neck bolster Facial Neck Bolster

GUARANTEES:

Structure 10 yr. on replacement parts for frame/structure and 1 yr. on labor Motor & controls 2 yr. warranty on materials for mechanical/electrical parts

Vinyl & foam **WEIGHTS**:

Table weight 160 lbs.

Shipping weight - boxed 213 lbs.

Rev 2/11

www.TouchAmerica.com (800) 678-6824 · (919) 732-6968 PO Box 1304 · Hillsborough · NC 27278

