

Olympus™ Flat Top



FLAT TOP:

Foam
Polyester batting
Upholstered top & frame
Subframe
Leg Frame

One-piece upholstered top, square corners, 3 layer foam
3/4" firm bottom, 1- 3/4" medium middle, urethane polymer
1/2" fluffy polyester Dacron top layer
30" width x 73" length x 6" thickness
None
20.5" width x 56.5 length x 5" thickness

TOP OPTIONS:

Footrests and face supports

No extra holes needed
Deluxe FaceSpace II recommended for prone massage

VINYL CHOICES:

Ultra Soft Touch - standard

Lightly textured, Super Soft Urethane vinyl, fabric backed, environmentally friendly

BASE:

Outside leg spacing
Inside leg spacing
Base materials
Parallel Lift Bars
Adjustable leg extension
Height range
Leg Recess

Maximum leg and knee room and maximum height range

25" width x 56" length
20" width x 51" length
Maple legs with 3/4" plywood
Two powder-coated carbon steel lift bars connect to motor
1/4" leg bolts w/ 2 knobs, 11 holes, felt backed, 2 rubber bumpers per leg
19" to 41" Double adjustable: 10" manual (ext. legs) & 12" electric lift
4" Recess on sides, 12" recess from head section

ELECTRIC LIFT:

Lift mechanism
Motor - Linak or Dewart
Power consumption
Control
240-volt model (international)

One 24 volt motor/actuator powered through a 110 volt, 5 amp transformer
24 VDC permanent magnet motor, UL listed
Linak, 4 amps; Dewart 5 amps max.
Foot pedal
Available at extra charge

BASE OPTIONS:

Extra-low-range legs

14" to 24" (electric lift only, short non-adjusting legs replace ext. legs)

GUARANTEES:

Structure
Vinyl & Foam
Motor/actuator & transformer

5 yrs.
Guaranteed to arrive in good condition
1 yr.

WEIGHTS:

Weight: 79 lbs.

